



Underwriters Laboratories Inc. (UL) Listings

COUNTRY	Cat No.	Wire Range Awg Cu Sol	Wire Range Awg Cu Str	Tightening Torque Wire Binding Screw In. - Lbs	Tightening Torque Armored Cable Clamp Screw In. - Lbs	Cu Ground Rod Diameters Inc	Pipe Size Inc	Armoured Ground Cable Diameters Inc
* USL	99	8 - 6	4	50	50	5 / 8, 1	1 / 2 Through 1	8 AWG - 0.1285 6 AWG - 0.162 4 AWG - 0.2043
* CNL	99	8 - 6	4	50	50	5 / 8, 1	1 / 2 Through 1	8 AWG - 0.1285 6 AWG - 0.162 4 AWG - 0.2043

The MVP99 Ground Clamp **VS** The " Old " Ground Clamp

" THE NEW "



1. Underwriters Laboratories Inc. (UL) Listed
2. Heavy Duty
3. Slightly heavier than the Old Ground Clamp
4. Complies with all 2008 NECA Regulations
5. Has Two (2) Straps for holding Armor in place
6. Fast & Quick installation of armor wire in place ** (3 - 5 min. install time) **
7. You **ONLY** need One (1) #99 for **EVERY** Two (2) Old Ground Clamps
8. The Cost ** \$ \$ ** of (1) #99 is Equal to the Cost of (2) Old Ground Clamps
9. Saves Time & Money, Finishes the Job Quicker
10. For Residential, Commercial and Industrial Use
11. No need for Armor removal from Wire
12. For Ground Rods, Metal and Copper Pipes (1 / 2 - 1 inch)
13. Used for Armor Cable #'s 8, 6 and 4 ** USA and Canada **
14. If you need **Five (5) Old Ground Clamps** for a Electrical Panel Installation YOU will **ONLY** need **Two (2) #99's** and **One (1)** Old Ground Clamp
15. Comes with Four (4) 10 / 24 Stainless Steel Screws for the Two (2) Straps giving it the ability to with stand a pressure of 50 psi
16. Has Two (2) built in Ribs to allow for greater and stronger hold on the Armor

" THE OLD "



1. Canadian Standards Association (CSA) Listed
2. Underwriters Laboratories Inc. (UL) - Listed
3. Slightly lighter than the MVP #99
4. Over 30 years old
5. Has One (1) Strap for holding Armor in place
6. Installation is Not Fast & Quick of armor wire in place (15 - 30 min install time)
7. It takes Longer to finish the job
8. Very difficult to work with when having to attach two (2) ground clamps
9. You must remove the Armor from Wire at all times for installation
10. For Ground Rods, Metal & Copper Pipes (1 / 2 - 1 inch)
11. Used for Armor Cable #'s 8, 6 and 4 USA & Canada
12. Does Not have 10 / 24 Stainless Steel Screws for Strap